



1000LM  
1400LM  
1900LM

# FLOOD ROUND

WORK  
LAMP  
LAVORO

## SPECIFICHE TECNICHE

- > **VOLTAGGIO:**  
MULTI-VOLTAGE 11-70VDC
- > **ASSORBIMENTO:**  
MAX. 1,6A (1000LM); MAX. 1,8A (1400LM); MAX. 2A (1900LM)
- > **SORGENTE LUMINOSA:**  
6 LED DA 1W
- > **USCITA LED**  
1000LM; 1400LM; 1900LM

## SPECIFICATIONS

- > **VOLTAGE:**  
MULTI-VOLTAGE 11-70VDC
- > **CURRENT:**  
MAX. 1,6A (1000LM); MAX. 1,8A (1400LM); MAX. 2A (1900LM)
- > **BULB:**  
1W LED x 6PCS
- > **LED OUTPUT:**  
1000LM; 1400LM; 1900LM

## CARATTERISTICHE

- > **TECNOLOGIA:**  
LED FINO A 100.000 ORE DI UTILIZZO  
FARO A LUCE DIFFUSA
- > **PROTEZIONE:**  
PROTETTO CONTRO L'INVERSIONE DI  
POLARITÀ  
RESISTENTE ALLE INTEMPERIE E ALLE  
VIBRAZIONI
- > **DESIGN:**  
INVOLUCRO IN ALLUMINIO PER UTILIZZI  
ESTREMI

CERTIFICAZIONE SAE  
CERTIFIED EMC




COD.  
PLS110083-0 1000 LUMEN  
PLS110083-1 1400 LUMEN  
PLS110083-2 1900 LUMEN

## FEATURES

- > **TECHNOLOGY:**  
LEDS RATE TO 100.000 HOURS OF  
OPERATION.  
WIDE BEAM
- > **PROTECTION:**  
REVERSE POLARITY PROTECTION  
WHEATERPROOF AND VIBRATION  
RESISTANT
- > **DESIGN:**  
HEAVY-DUTY POWDER COATED DIE  
CAST ALUMINUM

## DIMENSIONI/ DIMENSIONS:



## APPLICAZIONI / APPLICATIONS:

